



COMXCHANGE S-SERIES CONTROLLER

All-Inclusive IP Communications Server

The ComXchange S-Series controller is a 1U rack-mountable appliance utilizing best-in-class hardware components.

PHYSICAL

DIMENSIONS	16.8" W x 1.7" H x 14.0" D (1U)
WEIGHT	13 lbs

HARDWARE

CPU	Intel XEON Dual-Core
RAM	4 GB
HARD DRIVE	80 GB SSD
NETWORK	Quad 100/1000 NICs
SERIAL	Dual RS-232 Serial
USB 2.0 PORTS	4

TELEPHONY

MAXIMUM DEVICES (IP AND/OR ANALOG)	750
MAXIMUM TRUNKS	100*
MAXIMUM SIMULTANEOUS CALLS	100+*
MAXIMUM SIMULTANEOUS WAKE-UP CALLS	100*
MAXIMUM EMBEDDED VOICEMAIL BOXES	1500
MAXIMUM ACD AGENTS	15
MAXIMUM CONSOLE DEVICES	Available on any qualifying Device
CONFERENCE BRIDGE CAPACITY	Up to 5 bridges, with 10 callers per bridge*

SYSTEM POWER

LOAD VOLTAGE	120
AMP DRAW	0.95
POWER SUPPLY RATED WATTAGE	260

*Dependant on type of calls, codecs used, transcoding requirements, IVR usage and application usage. Consult a sales engineer for additional information.

TECHNICAL DATA SHEET

ENVIROMENTAL REQUIREMENTS

OPERATING TEMP. RANGE	10 to 35 °C (50 to 95 °F)
NON-OPERATING TEMP. RANGE	-40 to 70 °C (-40° to 158 °F)
HUMIDITY RANGE	8 to 90% non-condensing
NON-OPERATING HUMIDITY RANGE	5 to 95% non-condensing
MAXIMUM BTU OUTPUT	390.37

CO-RESIDENT ADD-ON MODULES SUPPORTED

INNCHARGE CALL ACCOUNTING	Yes
HOTELMGR WORKFLOW MANAGEMENT	Yes
PRIVATLINE DID MODULE	Yes
ORDERLYSTATS ACD REPORTING	Yes

INNOVATION™

TECHNOLOGIES WORLDWIDE, INC.

Innovation Technologies Worldwide, Inc.
1841 Bourbon Road · P.O. Box 183
Cross Plains, Wisconsin 53528 USA
Toll-free 800.424.6757
phone 608.798.3555 · fax 608.798.3567

www.innovationtw.com